

TRANSACTION REPORT

P. 01

NOV-09-2001 FRI 11:43 AM

FOR: HARTER, SECREST & EMERY 716 232 2152

DATE	START	RECEIVER	TX TIME	PAGES	TYPE	NOTE	M#	DP
NOV-09	11:17 AM	0581#85939*000140#91 7033051086#	25' 39"	57	SEND	OK	225	

TOTAL : 25M 39S PAGES: 57



HARTER, SECREST & EMERY, LLP
ATTORNEYS AND COUNSELORS
WWW.HSELAW.COM

November 9, 2001

TO	COMPANY	TELEPHONE	FACSIMILE
Vickie Beach	United States Patent & Trademark Office Washington, D.C.	703-308-1193	703-305-1086

FROM	COMPANY	TELEPHONE	FACSIMILE
Brian B. Shaw OUR FILE: 581/85939.000140	HARTER, SECREST & EMERY LLP	716-231-1193	716-232-2152

TOTAL NUMBER OF PAGES SENT (INCLUDING THIS COVER SHEET): 191 page(s)

MESSAGE OR SPECIAL INSTRUCTIONS:

PART TWO OF FOUR PARTS

MODE = MEMORY TRANSMISSION

START=NOV-09 14:49

END=NOV-09 15:14

FILE NO. = 122

STN NO.	COM	ABBR NO.	STATION NAME/TEL. NO.	PAGES	DURATION
001	OK	2	917033051086	050/050	00:21'22"

-HARTER SECREST EMERY -

***** -

- ***** -

716 232 2152- *****

15
Brian Shaw



HARTER, SECREST & EMERY, LLP
ATTORNEYS AND COUNSELORS
WWW.HSELAW.COM

November 9, 2001

TO	COMPANY	TELEPHONE	FACSIMILE
Vickie Beach	United States Patent & Trademark Office Washington, D.C.	703-308-1193	703-305-1086

FROM	COMPANY	TELEPHONE	FACSIMILE
Brian B. Shaw	HARTER, SECREST & EMERY LLP	716-231-1193	716-232-2152

OUR FILE: 581/85939.000140

TOTAL NUMBER OF PAGES SENT (INCLUDING THIS COVER SHEET): 191 page(s)

MESSAGE OR SPECIAL INSTRUCTIONS:

PART FOUR OF FOUR PARTS

IF YOU DID NOT RECEIVE THE NUMBER OF PAGES SHOWN ABOVE, OR IF ANY COPIES ARE ILLEGIBLE,
PLEASE CALL THE TELECOMMUNICATIONS OPERATOR AT 716-231-1498

THE INFORMATION CONTAINED IN THIS FACSIMILE MESSAGE IS PRIVILEGED AND/OR CONFIDENTIAL AND IS INTENDED ONLY FOR THE USE OF THE
INDIVIDUAL OR ENTITY NAMED ABOVE. IF THE READER OF THIS MESSAGE IS NOT THE INTENDED RECIPIENT OR THE EMPLOYEE OR AGENT RESPONSIBLE TO
DELIVER IT TO THE INTENDED RECIPIENT, YOU ARE HEREBY NOTIFIED THAT ANY DISSEMINATION, DISTRIBUTION OR COPYING OF THIS COMMUNICATION IS
STRICTLY PROHIBITED. IF YOU HAVE RECEIVED THIS MESSAGE IN ERROR, PLEASE NOTIFY US IMMEDIATELY BY TELEPHONE AND RETURN THE ORIGINAL
MESSAGE TO US AT THE ABOVE ADDRESS VIA THE U.S. POSTAL SERVICE. THANK YOU.

1600 BAUSCH & LOMB PLACE ROCHESTER, NEW YORK 14604-2711 PHONE: 716.232.6500 FAX: 716.232.2152

ROCHESTER, NEW YORK • BUFFALO, NEW YORK • ALBANY, NEW YORK • NAPLES, FLORIDA • FORT MYERS, FLORIDA • NEW YORK, NEW YORK

TRANSACTION REPORT

P. 01

NOV-09-2001 FRI 12:05 PM

FOR: HARTER, SECREST & EMERY 716 232 2152

DATE	START	RECEIVER	TX TIME	PAGES	TYPE	NOTE	M#	DP
NOV-09	11:46 AM	0581#85939*000140#91 7033051086#	18'01"	43	SEND	OK	228	

TOTAL : 18M 1S PAGES: 43



HARTER, SECREST & EMERY, LLP
ATTORNEYS AND COUNSELORS
WWW.HSELAW.COM

November 9, 2001

TO	COMPANY	TELEPHONE	FACSIMILE
Vickie Beach	United States Patent & Trademark Office Washington, D.C.	703-308-1193	703-305-1086

FROM	COMPANY	TELEPHONE	FACSIMILE
Brian B. Shaw	HARTER, SECREST & EMERY LLP	716-231-1193	716-232-2152

OUR FILE: 581/85939.000140

TOTAL NUMBER OF PAGES SENT (INCLUDING THIS COVER SHEET): 191 page(s)

MESSAGE OR SPECIAL INSTRUCTIONS:

PART THREE OF FOUR PARTS

PATENTS

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Willett, Kevin R.

Atty. Docket: 85939.000193

Serial No.: 09/839,887

Examiner:

Filed: April 20, 2001

Art Unit:

Title: CONTIGUOUS COLLIQUEFACTION FORMING A SURFACE FILM FOR A COMPOSITE STRIP

PRELIMINARY AMENDMENT

Commissioner of Patents and Trademarks
Washington, D.C. 20231

Sir:

Prior to substantive examination of the present application, please consider the application amended as follows:

- Sub A/B
1. (Once Amended) An automotive weatherseal, comprising:
 - (a) a resilient elastomeric body; and
 - (b) a colliquefied powder coating forming a contiguous surface film on a portion of the resilient elastomeric body, the surface film having a thickness less than 0.2 mm.
 2. (Once Amended) The automotive weatherseal of Claim 1, wherein the resilient elastomeric body includes a trim portion and a sealing portion.
 3. (Once Amended) The automotive weatherseal of Claim 1, wherein the surface film has a thickness between approximately 0.05 mm and 0.2 mm.
 4. (Once Amended) The automotive weatherseal of Claim 1, further comprising a metallic reinforcing member connected to the resilient body.
 5. (Once Amended) An automotive weatherseal, comprising:
 - (a) a substrate having a first portion formed of a first elastomeric material and a second portion formed of a different second elastomeric material; and

(b) a powder coating colliquiefaction forming a contiguous surface layer bonded to the first portion and the second portion.

6. (Once Amended) The automotive weatherseal of Claim 5, wherein the first elastomeric material is a thermoset material and the second elastomeric material is a thermoplastic material.

7. (Once Amended) The automotive weatherseal of Claim 5, further comprising a metallic reinforcing member connected to one of the first portion or the second portion.

8. (Once Amended) The automotive weatherseal of Claim 5, wherein the colliquiefaction has a thickness between approximately 0.05 mm and 0.2 mm.

9. (Once Amended) The automotive weatherseal of Claim 5, wherein the colliquiefaction is a thermoset material and the second elastomeric material is a thermoplastic material.

10. (Once Amended) A weatherseal comprising a colliquiefaction of a powder coating defining a contiguous surface film on a resilient elastomeric portion of the weatherseal.

11. The weatherseal of Claim 10, wherein the powder coating includes a thermoset and a thermoplastic material.

12. The weatherseal of Claim 10, wherein the colliquiefaction is a thermoset material and the weatherseal includes a thermoplastic portion bonded to the colliquiefaction.

13. The weatherseal of Claim 10, further comprising a metallic reinforcing member.

14. The weatherseal of Claim 10, further comprising a thermoplastic portion and a thermoset portion, and the colliquiefaction is bonded to the thermoplastic portion and the thermoset portion.

15. The weatherseal of Claim 10, wherein the colliquiefaction has a thickness less than the 0.2 mm.

16. The weatherseal of Claim 10, further comprising a metallic reinforcing member having a U-shaped cross sectional profile.

17. The weatherseal of Claim 10, wherein the contiguous colliqufaction is continuous.

A25ub
R3
18. (Once Amended) The weatherseal of Claim 10, wherein the colliqufaction is located to form a sealing surface.

19. (Once Amended) The weatherseal of Claim 10, wherein the colliqufaction has a gloss appearance.

20. (Once Amended) A weatherseal for sealing an interface between two confronting surfaces in an automotive vehicle, the weatherseal comprising;

(a) an elastomeric base;

(b) a resilient sealing portion for contacting one of the confronting surfaces;

and

(c) a colliqufication of a powder coating forming a contiguous surface film on one of the base and the sealing portion.

21. (Once Amended) ~~The weatherseal of Claim 20, wherein the surface film is on the sealing portion.~~

22. (Once Amended) ~~The weatherseal of Claim 20, wherein the sealing portion is elastomeric and the surface film is on the sealing portion.~~

5B4
23. (Once Amended) ~~The weatherseal of Claim 20, wherein the base includes a trim portion and the colliqufaction is located on the trim portion.~~

24. (Once Amended) ~~The weatherseal of Claim 20, further comprising a metallic reinforcing member in the base.~~

25. (Once Amended) ~~The weatherseal of Claim 20, wherein the colliqufaction is bonded to the one of the base and the sealing portion to preclude non-destructive separation.~~

Sub 35
AZ
corr

26. (Once Amended) The weatherseal of Claim 20, wherein the base further comprises a trim portion formed of a different material than the sealing portion, and the colliquescence is bonded to the trim portion.

27. A method of forming a surface film on a portion of a weatherseal, comprising:

- (a) creating an electric potential between the portion of the weatherseal and powder coating;
- (b) exposing the powder coating to the electric potential to attach the powder coating to the portion of the weatherseal; and
- (c) melting the powder coating on the portion of the weatherseal to form a contiguous surface layer on the portion of the weatherseal.

28. The method of Claim 27, further comprising employing a thermosetting material in the powder coating.

29. A method of forming a surface film on a weatherseal, comprising:

- (a) forming a resilient body about an electrically conductive member;
- (b) exposing the electrically conductive member to an electrical potential to form a surface charge on the resilient body;
- (c) exposing the surface charge on the resilient body to an oppositely charged powder coating to attract the powder coating to the resilient body; and
- (d) melting the powder coating on the resilient body to form a contiguous surface layer bonded to the body.

30. A method of forming a contiguous surface film on a weatherseal, comprising:

- (a) retaining a powder coating on the weatherseal; and
- (b) colliquescing the retained powder coating to form a contiguous surface film.

31. The method of Claim 30, further comprising electrostatically retaining the powder coating on the weatherseal.

32. The method of Claim 31, further comprising forming the weatherseal of a polymeric material.